

El terminal de mano **ecoLite EMV** con sistema operativo **seguro Android 11.0** viene con una **pantalla TFT IPS LCD color** de alta definición de **6.0"**, **impresora térmica** industrial y configuración flexible para varios escenarios. Admite una amplia gama de opciones de conectividad **2G/3G/4G**, localización **GPS**, así como también **NFC** sin contacto incorporado, **BT5.0** y **WIFI**.

Potenciado por su CPU de cuatro núcleos y amplia memoria, el terminal **ecoLite EMV** tiene un procesamiento excepcionalmente rápido de las aplicaciones. Opcionalmente puede admitir características adicionales como **escáner de código de barras y QR**, lector de **huella digital**, certificación **EMVco** o número fiscal de algunos países.



Es la elección inteligente para el **pago y el servicio de ventanilla única**.

Funcionalidades

- Venta y validación de billetes abordo.
- Venta de billetes en taquilla.
- TPV para RdR (Red de Recargas)
- Terminal de inspector.
- Localización de bus en tiempo real.
- Impresión de billetes o recibos.
- Pago único de MSR/ICCR/NFC, con certificación PCI PTS 6.X, EMV L1&L2, Paypass, Paywave, Amex y TQM



Especificaciones

Basic Characteristics	OS	Safedroid OS (based on Android 11.0) GMS certified
	CPU	1.8GHz Quad-Core ARM Cortex-A53
	ROM	16GB ROM EMMC
	RAM	2GB RAM LPDDR
	Display	6.0-inch TFT IPS LCD, resolution 1440*720
	Panel	Ultra-sensitive capacitive touch screen, can work with gloves and wet fingers
	Dimensions	224mm X 84mm X 18mm (max 51mm)
	Weight	410g (Battery included)
	Keys	Physical keys: Power on/off, Volume + /-, Scan
	Input	Chinese/English, and supports handwriting and soft keyboard
	WIFI	IEEE 802.11 a/b/g/n/ac, support 2.4GHz and 5GHz
	Bluetooth	BT 5.0 and earlier

Radio Communication	4G	European version (Default): FDD-LTE: B1/B3/B7/B8/B20/B28 TDD-LTE: B38/B40/B41
	3G	European version (Default): WCDMA: B1/B8
	2G	European version (Default): GSM/GPRS/EDGE: 900/1800MHz
Payment	Magcard reader	Supports ISO7811/7812/7813, and supports triple track (tracks 1/2/3), bi-directional
	Smart Card reader	Supports ISO7816 standard
	Contactless Card reader	Supports 14443A/ 14443B
Expansion and peripherals	Printer	High-Speed Thermal Printer; 58mm printing paper, 40mm paper roll
	Rear Camera	5MP camera with LED flash and auto-focus function
	Satellite Positioning	Support GPS(A-GPS)/ Bei-Dou/ Glonass or Galileo
	LEDS	3 colors are used to indicate
	Audio	Speaker, Microphone, Buzzer
Interfaces	Micro SD Card Slot	1 Pcs
	SIM Card Slot	1 Pcs Micro SIM
	PSAM Card Slot	2 Pcs Conforms to ISO7816 standard
	USB Port	1 Pcs Type C USB
Power	Battery	Li-ion battery, 7.6V/2600mAh
	Charging Port	Type C USB Port, 5V DC/2A
Environment	Operating Temperature	-10°C to 50°C
	Storage Temperature	-20°C to 70°C
	Humidity	5% to 95% Relative Humidity, Non-Condensing
Certification	Electromagnetic	CE, RoHS, FCC, EMV L1 & L2

